

BASIC WALL SOUNDPROOFING FRAME SYSTEM

from Album of Typical Technical Solution
TechnoSonus and NIISF version
TS/01.2020/RD/S/R4 type TS-2.1

SYSTEM
THICKNESS
69 mm



GENERAL CONSTRUCTION
SOUND REDUCTION INDEX
Rw = 58-62 dB

AIRBORNE
SOUND REDUCTION
IMPROVEMENT INDEX

▲ Rw = 13-12 dB



1. ACOUSTIC GYPS (GKLZ)
2. SOUND ABSORBING BOARDS STOPZVUK
3. SEALING TAPE
4. SONOKREP
5. METAL FRAME
6. TERMOZVUKOIZOL
7. STOPZVUK V100 TAPE

DESCRIPTION

First-level soundproofing system. It is recommended for use in multi-apartment houses or private residences. The system ensures the reduction of domestic noise level to the standard values, specified in SP 5.13330.2011 "Noise Protection" (SNiP 23-03-2003 Revised Version).

COMPONENTS

Material	Coefficient per 1 m ² *
TermoZvukolzol Standard Soundproofing Mat (10m x 1.5m x 14mm) 15m ²	0,0767
StopZvuk BP Prime sound absorbing board (1m x 0.6m x 27mm) 8pcs. 4.8m ²	0,2083
Sonokrep Protector anti-vibration hanger	3,3000
Sonetic vibroacoustic sealant , 310ml	0,2500
Bautger adhesive, 10 l /8kg container	0,0250
Vibration cushioning band V-100 (30m x 100mm x 4mm)	0,0450
Reinforced tape (50m x 50mm)	0,0380
Sealing Band DB (30m x 50mm x 2.5mm)	0,1235
Vibration isolation washer (14mm x 5mm) + metal washer (M6) 50 pcs.	0,1429
AcousticGyps PPN reinforced profile 27/28, 3m	0,4500
AcousticGyps PP reinforced profile 60/27, 3m	1,2000
AcousticGyps soundproofing gypsum board (2m x 1.2m x 12.5mm) 2.4m ²	0,9167
Self-threading screw TC-XTN 3.9x38 (500 pcs.)	0,0800
Self-threading screw TC-XTN 3.9x23 (500 pcs.)	0,0500
Self-threading screw TC-MM 4.2x13 (1000 pcs.)	0,0150
AcousticGyps single-level connector (Crab) for PP 60/27	4,0000
Dowel nail TC-DG 6/60 (100 pcs.)	0,0700

*Coefficients are advisory in nature, calculated empirically