

## PREMIUM P PARTITION SOUNDPROOFING SYSTEM (DOUBLE FRAME)



SYSTEM  
THICKNESS  
**158 mm**



GENERAL CONSTRUCTION  
SOUND REDUCTION INDEX  
**Rw = 62 dB**



### DESCRIPTION

The most common and highly demanded system for rooms partitioning. Used in multi-apartment buildings of enhanced comfort, hotels, offices, conference rooms, etc. The system ensures the best soundproofing effect against airborne noise. The main system element are thin and heavy panels Sonoplat.

### COMPONENTS

Material	Coefficient per 1 m <sup>2</sup> *
Sonoplat Standard Plus Panel (1,2 m x 0,8m x mm) 0,96m <sup>2</sup>	2,1875
StopZvuk BP Premium Sound Absorbing Board (1m x 0.6m x 50mm) 4pcs., 2.4m <sup>2</sup>	0,8334
Sonetic Vibroacoustic Sealant 310ml	0,5000
SonoPlat Band (40m x 50mm) w/o logo	0,1538
Vibration Cushioning Band V-100 (30m x 100mm x 4mm)	0,0900
Vibration Isolation Washer (14mm x 5mm) + Metal Washer (M6) 50 pcs.	0,2000
Sealing Band DB (30m x 50mm x 2.5mm)	0,2470
AcousticGyps PN Reinforced Profile 50/40, 3m	0,9000
AcousticGyps PS Reinforced Profile 50/50, 3m	3,2000
AcousticGyps Soundproofing Gypsum Board (2m x 1.2m x 12.5mm) 2.4m <sup>2</sup>	0,9167
Self-Threading Screw TC-M 3.5x25 (500 pcs.)	0,1000
Self-Threading Screw TC-XTN 3.9x38 (500 pcs.)	0,1600
Self-Threading Screw TC-MM 4.2x13 (1000 pcs.)	0,0300
Dowel Nail TC-DG 6/60 (100 pcs.)	0,1400

\*Coefficients are advisory in nature, calculated empirically