

STANDARD P CEILING SOUNDPROOFING FRAME SYSTEM

from Album of Typical Technical Solution
TechnoSonus and NIISF version
TS/01.2020/RD/S/R4 type TS-3.2



SYSTEM
THICKNESS
90 mm



GENERAL CONSTRUCTION
SOUND REDUCTION INDEX
Rw = 69 dB



AIRBORNE
SOUND REDUCTION
IMPROVEMENT INDEX
▲ Rw = 18 dB



IMPACT
SOUND REDUCTION
IMPROVEMENT INDEX
▲ Lnw = 15 dB



DESCRIPTION

The second-level soundproofing system. The most common and demanded system. It is recommended for use in multi-apartment residential buildings of enhanced comfort, hotels, hospitals, health centres, etc. The system ensures the best soundproofing effect against airborne noise and significantly reduces structure-borne noises. The main system elements are thin and heavy panels SonoPlat.

COMPONENTS

Material	Coefficient per 1 m ² *
SonoPlat Standard Plus Panel (1.2m x 0.8m x 12mm) 0.96m ²	1,0938
TermoZvukolzol Standard Soundproofing Mat (10m x 1.5m x 14mm) 15m ²	0,0767
StopZvuk BP Premium Sound Absorbing Board (1m x 0.6m x 50mm) 4pcs., 2.4m ²	0,4167
Sonokrep Protector Anti-Vibration Hanger	3,3000
Sonetic Vibroacoustic Sealant , 310ml	0,0250
Bautger Adhesive, 10 l /8kg container	0,0769
SonoPlat band (40m x 50mm) w/o logo	0,0450
Vibration Cushioning Band V-100 (30m x 100mm x 4mm)	0,0380
Reinforced Tape (50m x 50mm)	0,1235
Sealing Band DB (30m x 50mm x 2.5mm)	0,1429
Vibration Isolation Washer (14mm x 5mm) + Metal Washer (M6) 50 pcs.	0,1429
AcousticGyps PPN Reinforced Profile 27/28, 3m	0,4500
AcousticGyps PP Reinforced Profile 60/27, 3m	1,2000
AcousticGyps Soundproofing Gypsum Board (2m x 1.2m x 12.5mm) 2.4m ²	0,4583
Self-Threading Screw TC-M 3.5x25 (500 pcs.)	0,0500
Self-Threading Screw TC-XTN 3.9x38 (500 pcs.)	0,0800
Self-Threading Screw TC-MM 4.2x13 (1000 pcs.)	0,0150
AcousticGyps single-level connector (Crab) for PP 60/27	4,0000
AcousticGyps extension for PP 60/27	0,6000
Dowel Nail TC-DG 6/60 (100 pcs.)	0,0700

*Coefficients are advisory in nature, calculated empirically